

Experience unmatched network visibility and extreme performance.

Accelerate resolution of your critical issues with the most efficient solution on the market.

Contact us today at **sales@allegro-packets.com** to schedule a free consultation!




Allegro Packets
Network Multimeter

The All-in-one Solution for Network Troubleshooting



Thousands of IT experts trust in Allegro Packets



Advantages

High-granular network visibility from Layer 2 to 7 in real time and capture rates up to 240 Gbps / 60 Mpps.



Very simple installation and setup, with a consistent software platform and intuitive GUI.



Extreme performance for up to 400 Gbps network links even in a compact 1U form factor for minimizing your carbon footprint.



Highly flexible and expandable architecture for seamless upgrades from 1 G to 400 G interfaces and storage expansion.



Capture months' worth of network traffic data and replay specific timeframes or filtered packets on-demand.



Security through two-factor authentication, data-at-rest encryption, and granular user access controls.



Portable

Rackmount

500 / 510

Performance	Average throughput (capture only / full decode): 4 / 2 4 / 2.5 Gbit/s
	Average packets per second: 500,000 600,000 pps
Physical	4 x 10 / 100 / 1000Base-T 2 x 2.5G and 2 x 10 / 100 / 1000Base-T Capture Ports
	In-Memory 4 GB / 8 GB 16 GB
	1 kg, 148 x 44 x 118 (W / H / D in mm)



Capture rate ↑ 4 Gbps

Packet storage ↑ 15.3 TB



x210 series

Performance	3 performance levels available (1210 / 3210 / 5210)
	Average throughput (full decode): 12 / 30 / 60 Gbit/s
Physical	Average packets per second (capture only / full decode): 7.5 / 3 Mpps 15 / 6 Mpps 25 / 12 Mpps
	6-8 kg, 436.88 x 44.5 x 429.3 (W / H / D in mm)



4 x SFP+ Capture ports
2 regular extension slots for network extension cards

In-Memory 32 / 96 GB, expandable up to 576 GB

Physical



Capture rate ↑ 120 Gbps

Packet storage ↑ 106 TB

x310 series

Performance	4 performance levels available (1310 / 3310 / 5310 / 7310)
	Average throughput (full decode): 20 / 40 / 80 / 120 Gbit/s
Physical	Average packets per second (capture only / full decode): 10 / 4 Mpps 15 / 7 Mpps 30 / 15 Mpps 60 / 30 Mpps
	2 x SFP+ Capture ports + 3 NICs
	In-Memory 192 GB, expandable up to 6 TB
	Packet Ring buffer storage configurable with 12 x 2.5" SATA / U.2 slots
	20-30 kg, 437 x 43 x 597 (W / H / D in mm)



Capture rate ↑ 240 Gbps

Packet storage ↑ 307 TB



810

Performance	Average throughput (capture only / full decode): 6 / 3.5 Gbit/s
	Average packets per second (capture only / full decode): 1 Mpps / 600 kpps
Physical	2 x SFP28 and 3 x 1000Base-T Capture Ports
	In-Memory 16 GB, expandable up to 256 GB
	2 kg, 254 x 43 x 226 (W / H / D in mm)
	Available also as 1U rack unit



Capture rate ↑ 6 Gbps

Packet storage ↑ 33.6 TB



Allegro Packets

Network Multimeter

x410 series

Performance	4 performance levels available (1410 / 3410 / 5410 / 7410)
	Average throughput (full decode): 20 / 40 / 80 / 120 Gbit/s
Physical	Average packets per second (capture only / full decode): 10 / 4 Mpps 15 / 7 Mpps 30 / 15 Mpps 60 / 30 Mpps
	2 x SFP+ Capture ports + 7 NICs
	In-Memory 192 GB, expandable up to 6 TB
	Packet Ring buffer storage configurable with 12 x 3.5" SATA3 / U.2 slots
	20-32 kg, 437 x 89 x 648 (W / H / D in mm)



Capture rate ↑ 240 Gbps

Packet storage ↑ 307 TB



1010 / 3010

Performance	2 performance levels available (1010 / 3010)
	Average throughput (capture only / full decode): 20 / 10 20 / 20 Gbit/s
Physical	Average packets per second (capture only / full decode): 4 / 1.2 Mpps 4 / 4 Mpps
	2 x SFP28 and 3 x 1000Base-T Capture Ports
	In-Memory 16 GB / 64 GB, expandable up to 256 GB
	2 kg, 254 x 43 x 226 (W / H / D in mm)




Capture rate ↑ 20 Gbps

Packet storage ↑ 33.6 TB



x510 series

Performance	4 performance levels available (1510 / 3510 / 5510 / 7510)
	Average throughput and Average packets per second like x410 series
Physical	Completely configurable, 4 NICs (no default capture ports)
	In-Memory 192 GB, expandable up to 3 TB
	36 x 3.5" SATA3 / SAS3 slots
	40-80 kg, 437 x 178 x 699 (W / H / D in mm)



Capture rate ↑ 200 Gbps

Packet storage ↑ 678 TB

